





特點

- 一體式設計(不可更換燈泡)
- 全系列採用純色高亮度LED
- 交流指示燈允許電壓波動 $\pm 10\%$
- 連續工作壽命>30000小時
- 頭部防護等級IP40
- 外殼採用阻燃尼龍製作



規格

外型圖	型號品名	接點	燈泡電壓	顏色	尺寸圖
	E4.22F Δ -S 22Ø超短型指示燈 圓型	指示燈無 接點選項	☒ 1:AC.DC 6V ☒ 2:AC.DC 12V ☒ 3:AC.DC 24V ☒ 4:AC.DC 110V ☒ 5:AC.DC 220V	 R:紅  Y:黃  G:綠  B:藍  W:白	
	E4.22F Δ -S 22Ø超短型指示燈 圓型	指示燈無 接點選項	☒ 1:AC.DC 6V ☒ 2:AC.DC 12V ☒ 3:AC.DC 24V ☒ 4:AC.DC 110V ☒ 5:AC.DC 220V	 R:紅  Y:黃  G:綠  B:藍  W:白	
	E4.22F Δ -S 22Ø超短型指示燈 圓型	指示燈無 接點選項	☒ 1:AC.DC 6V ☒ 2:AC.DC 12V ☒ 3:AC.DC 24V ☒ 4:AC.DC 110V ☒ 5:AC.DC 220V	 R:紅  Y:黃  G:綠  B:藍  W:白	
	E4.22F Δ -S 22Ø超短型指示燈 圓型	指示燈無 接點選項	☒ 1:AC.DC 6V ☒ 2:AC.DC 12V ☒ 3:AC.DC 24V ☒ 4:AC.DC 110V ☒ 5:AC.DC 220V	 R:紅  Y:黃  G:綠  B:藍  W:白	
	E4.22F Δ -S 22Ø超短型指示燈 圓型	指示燈無 接點選項	☒ 1:AC.DC 6V ☒ 2:AC.DC 12V ☒ 3:AC.DC 24V ☒ 4:AC.DC 110V ☒ 5:AC.DC 220V	 R:紅  Y:黃  G:綠  B:藍  W:白	