

特點

- 零背隙
- 剛性大
- 材質：鋁合金
- 適合譯碼器、小馬力傳動機構、高精密傳動上
- 一體成型
- 偏角誤差較佳
- 不銹鋼材質扭力較佳
- 固定方式：止付螺絲固定式



規格

型 號	一般扭力 (N.m)	最大扭力 (N.m)	最高回轉速 (Rpm/min)	慣 性 (Kg·m ²)	容許偏心 (mm)	容許偏角 (°)	容許軸向位差 (mm)
SCT-8	0.1	0.2	48000	1.2×10^{-8}	0.10	2	±0.2
SCT-12	0.2	0.4	32000	8.3×10^{-8}	0.10	2	±0.3
SCT-16	0.3	0.6	24000	3.3×10^{-7}	0.10	2	±0.4
SCT-20	0.5	1.0	19000	9.0×10^{-7}	0.10	2	±0.4
SCT-25	1.0	2.0	15000	2.6×10^{-6}	0.15	2	±0.5
SCT-32	2.0	4.0	12000	9.6×10^{-6}	0.15	2	±0.5
SCT-40	5.0	10.0	9600	3.2×10^{-5}	0.20	2	±0.5
SCT-50	10.0	20.0	7700	1.0×10^{-4}	0.20	2	±0.5
SCT-63	20.0	40.0	6100	3.2×10^{-4}	0.20	2	±0.5

尺寸

型 號	D	I	L	G	M	d1xd2標準孔徑公差(H7)		重 量(g)
						Min	Max	
SCT-8	8	3.5	14.0	1.7	M2	2	4	1.3
SCT-12	12	5.0	18.5	2.5	M2.5	3	6	4.5
SCT-16	16	6.5	23.0	3.0	M3	4	8	9.5
SCT-20	20	7.5	26.0	3.0	M4	5	10	16.0
SCT-25	25	8.5	31.0	4.0	M4	5	12	30.0
SCT-32	32	12.0	41.0	6.0	M5	6	14	65.0
SCT-40	40	15	56.0	8.5	M5	8	20	120.0
SCT-50	50	18	71.0	10.5	M6	12	25	230.0
SCT-63	63	22	90.0	13.0	M8	15	35	470.0

訂購型號：SCT - ϕD - $\phi d1 \times \phi d2$

