





特點

- 類比式電壓輸出0-10V
- 防水等級IP-67
- 可檢測金屬之位移及距離
- 適用於自動化產業機械



規格

產品型號	PM-A1203	PM-A1807	PM-A3010
外形圖片			
外形尺寸(mm)	M12 x 1 x L50	M18 x 1 x L80	M30 x 1.5 x L80
檢測距離(mm)	0.1...3	1...7	5...10
螺母外形尺寸(mm)	A AF 17/4 Thick	A AF 25/4 Thick	A AF 36/5 Thick
出線連接方式	B	2m ø5 PVC 電線	
輸出方式	線性電壓	0~10V	
外形尺寸圖			
安裝方式	 埋入式	 非埋入式	 埋入式

標準檢測物(mm)	鐵板12 x 12 x t1	鐵板24 x 24 x t1	鐵板30 x 30 x t1
電源電壓(VDC)	18~30VDC · Ripple<10%		
輸出電壓(V)	0...10V		
線性度/重複精度	<5%(Sr) / 0.02mm		
消耗電流(mA)	<35mA (於24VDC空載時)		
負載電阻	≥2K Ω	≥4.7K Ω	
反應頻率(Hz)	100 Hz		
保護結構	IP-67		
反極性保護	具備		
環境溫度(°C)及濕度(RH)	-20~+70 · 35~85%		
外殼材質	銅鍍鎳		
產品認證	CE		

尺寸

	PM-A1203	PM-A1807	PM-A3010
接線圖	