

特點

- 荷重：20t
- 無電解鍍電鍍
- 鋼珠設計，抗側向力
- 材質為合金鋼
- 焊封方式密封
- 防水等級為IP68



規格

技術規格 Specification		
Rated Capacities capacity	額定荷重	20, 30, 40 (t)
Rated Output	額定輸出	20mV/V $\pm 0.25\%$
Non-linearity	非線性	0.03%F.S
Hysteresis	遲滯	0.03%F.S
Repeatability	重複性	0.03%F.S
20mins Creep/DR	蠕變/回零(20 分鐘)	0.02%F.S/10℃
Temperature Effect On Output	輸出溫度影響	0.03 %F.S/10℃
Temperature Effect On Zero	零點溫度影響	0.03 %F.S/10℃
Zero Balance	零點平衡	$\pm 0.0200\text{mV/V}$
Input Impedance	輸入阻抗	740 $\pm 15 \Omega$
Output Impedance	輸出阻抗	700 $\pm 5 \Omega$
Insulation Impedance	絕緣阻抗	$\geq 5000 \text{ M } \Omega$
Safe Overload	安全過載率	150 %F.S
Ultimate Overload	極限過載率	200 %F.S
Operating Temperature Range	工作溫度範圍	- 20~60℃
Recommended Excitation	建議工作電壓	5~12 VDC
Maximum Excitation	最大工作電壓	15 VDC
Construction	材質	鋼合金 Steel Alloy
Protection Class	防水等級	IP68
Cable	電纜線	$\Phi 6 \times 13 \text{ m}$
Mode of Connection	接線方式	紅：電源+，黑：電源-，綠：信號+，白：信號- Red (EXC+) ,Black (EXC-) ,Green (SIG+) ,White (SIG-)

尺寸

