

特點

- 材質為鋁合金
- 防水等級為IP65
- 工作溫度範圍:-20~+50°C
- 推薦安裝力矩:10N.m

規格



額定荷載	Ratedload	150 kg
靈敏度	Sensitivity	1.0 ± 0.2 mV/V,
蠕變(30分鐘)	Creep(30min)	±166ppm
零點平衡	Zero Balance	±3%Emax
零點溫度影響	Temperature Effect On Zero	±17.5ppm°C
輸出溫度影響	Temperature Effect On Output	+20°C~+40°C, ±17.5ppm°C -10°C~+20°C, ±11.67ppm°C
輸入阻抗	Input Impedance	1220 ± 15Ω
輸出阻抗	Output Impedance	1000 ± 5Ω
絕緣電阻	Insulation resistance	≥2000MΩ(50C DC)
工作溫度範圍	Operating Temperature Range	-20~+50°C
安全過載	Safe load limit	150 %F.S
極限過載	Ultimate load limit	300 %F.S
推薦激勵電壓	Recommend excitation	10V DC
最大激勵電壓	Maximum excitation	15V DC
材質	Construction	鋁合金 Aluminum
防水等級	Protection Class	IP65
電纜線	Cable	Length:0.5m Diameter:(排線flat cable)
接線方式	Mode of Connection	紅：電源+，黑：電源-， 綠：信號+，白：信號- Red (EXC+), Black(EXC-), Green (SIG+), White(SIG-) 或 黑：電源+，綠：電源-， 紅：信號+，白：信號- Black (EXC+), Green(EXC-), Red (SIG+), White(SIG-)

尺寸

