

特點

- 連結
- 能省線路
- 0~9999雙重表示
- 與DS系列能連結
- 緊密結合安裝可能
- 雙重支援嚴厲的檢出
- 雙重輸出功率、雙重顯示、靈敏度補正機能也雙重
- 雙重靈敏度補正機能"ASC"(自動靈敏度補正/復歸)



規格

光 源		4元素紅色LED			綠色LED			4元素紅色LED
種 類		單獨型	連結型親機	連結型子機	單獨型	連結型親機	連結型子機	單獨型
型 號		D2RF-TN	D2RF-TMN	D2RF-TSN	D2GF-TN	D2GF-TMN	D2GF-TSN	D2RF-TAN
		D2RF-TCN4	D2RF-TMCN4	D2RF-TSCN4	D2GF-TCN4	D2GF-TMCN4	D2GF-TSCN4	—
應答時間		60 μ s / 250 μ s / 2ns						
表 示 燈		出力表示(橙)x2(CH1•CH2)						
螢幕表示		紅色、綠色雙顯示						
制御出力		NPN 2 出力						
類比出力		—						
入力設定		外部入力						
機 能		時間 1~9000ms 可調						
出力形態		遮光 ON / 入光 ON 切換						
絕緣抵抗		20M Ω 以上						
定 格	電源電壓	DC 12~24V						
	消費電流	45Ma 以下 / 24V 時						
IEC規格		CE 適合						
耐環境性	耐振動	耐久：10~55Hz						
	耐衝擊	約 50g(500m/s ²) X,Y,Z 各方向2時間						
	保護構造、材質	IEC 規格：IP50						
質 量		65g						

尺寸

電纜類型

D2RF-TN,D2RF-TCN4,D2GF-TN,D2GF-TCN4,D2RF-TAN

Technical drawing of the D2RF cable assembly. The side view shows a cable length of 33.4, a mounting bracket width of 11, and a cable diameter of 7.8. The front view shows a total width of 68.9, a mounting bracket width of 10.5, a cable diameter of 7.2, and a mounting bracket thickness of 1.9. The detail view shows a cable diameter of 4.2, a mounting bracket width of 11.2, and a cable diameter of 8.65. The cable is labeled as 4芯×0.2mm² and the mounting bracket is labeled as M8 4ピンコネクタ.

ケーブル: 4芯×0.2mm²
アナログケーブル: 4.0 5芯×0.2mm²

连接器類型

D2RF-TMN,D2RF-TMCN4,D2GF-TMN,D2GF-TMCN4
D2RF-TSN,D2RF-TSCN4,D2GF-TSN,D2GF-TSCN4

Technical drawing of the D2RF connector assembly. The side view shows a cable length of 33.4, a mounting bracket width of 11, and a cable diameter of 7.8. The front view shows a total width of 68.9, a mounting bracket width of 10.5, a cable diameter of 7.2, and a mounting bracket thickness of 1.9. The detail view shows a cable diameter of 4.2, a mounting bracket width of 11.2, and a cable diameter of 8.65. The cable is labeled as 4芯×0.2mm² and the mounting bracket is labeled as M8 4ピンコネクタ.

ケーブル: 4芯×0.2mm²
アナログケーブル: 4.0 5芯×0.2mm²